

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
14 July 2005 (14.07.2005)

PCT

(10) International Publication Number
WO 2005/064682 A1

(51) International Patent Classification⁷: **H01L 27/148**

(21) International Application Number:
PCT/US2003/039026

(22) International Filing Date: 8 December 2003 (08.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **INTERNATIONAL BUSINESS MACHINES CORPORATION** [US/US]; New Orchard Road, Armonk, NY 10504 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ANDERSON, Brent, A.** [US/US]; 221 Cilley Hill Road, Jericho, VT 05465 (US). **BRYANT, Andres** [US/US]; 19 Wilkinson Drive, Essex Junction, VT 05452 (US). **NOWAK, Edward, J.** [US/US]; 8 Windridge Road, Essex Junction, VT 05452 (US).

(74) Agent: **ANDERSON, Jay, H.**; International Business Machines Corporation, Zip 482, 2070 Route 52, Hopewell Junction, NY 12533 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SEMICONDUCTOR MEMORY DEVICE WITH INCREASED NODE CAPACITANCE



(57) Abstract: An integrated circuit semiconductor memory device (100) has a first dielectric layer (116) characterized as the BOX layer or absent from a portion (130) of the substrate (112) under the gate of a storage transistor to increase the gate-to-substrate capacitance and thereby reduce the soft error rate. A second dielectric layer (132) having a property different from the first dielectric layer at least partly covers that portion (130) of the substrate. The device may be a FinFET device including a fin (122) and a gate dielectric layer (124, 126) between the gate and the fin, with the second dielectric layer having less leakage than the gate dielectric layer.